

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 3.5 gpf (13.2 Lpf) (3.5)

Power Type

Hardwired (HW) Battery

Water Efficiency

Low Consumption Water Saver

Bypass

Dual-Filtered Fixed Bypass Diaphragm

Override

True Mechanical (TMO)

Compliances & Certifications

ADA Compliant BAA Compliant BABAA Compliant UPC Certified cUPC Certified UL Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

Sloan® Exposed Sensor Water Closet Flushometer

FEATURES

- Flush volumes start as low as 1.6 gpf/6.0 Lpf
- Water conservation is aided by the ADA-compliant, non-holdopen handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandalresistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Sloan Exposed Installation Instructions
- Sloan Exposed (Spanish) Installation Instructions
- EBV 200 Smooth Installation Instructions
- EL 600-A Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide





- Tail Piece Repair and Maintenance Guide
- Sloan Flushometer Repair and Maintenance Guide
- EBV-200-A Repair and Maintenance Guide
- EL600A Smooth Side Mount Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com