

OPTIONS

Flush Volume

0.5 gpf (1.9 Lpf) (0.5)

Finish

Brushed Nickel (BN)
Brushed Stainless (SF)
Graphite (GR)
Polished Brass (PB)
Polished Chrome (CP)

Water Efficiency

High Efficiency
Low Consumption

Compliances & Certifications

ADA Compliant
BAA Compliant
UPC Certified
BABAA Compliant
LEED V4 Water Efficiency Credit
Satisfies LEED Credits
WaterSense Listed
cUPC Green Certified
cUPC Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard G2 RESS-U BT shown

DESCRIPTION

G2 Exposed Sensor Urinal Flushometer

FEATURES

- Wireless connected device for real time diagnostic and adjustable product settings
- Sloan Connect App® readily available for smart phone and tablet devices
- "Low Battery" Flashing LED
- Sweat solder adapter with cover tube and cast wall flange with set screw
- Four (4) Size AA Battery Power Source
- Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- Engineered Metal Cover with replaceable Lens Window
- PERMEX® Synthetic Rubber Diaphragm with Dual-Filtered Fixed Bypass
- Courtesy Flush® Override Button
- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

- [Additional Downloads](#)