



Royal® Sensor Flushometer

ROYAL 195 ESS

Product description

Royal® Concealed Sensor Hardwired Urinal Flushometer.

Compliances & Certifications



(ADA Compliant, BAA Compliant, BABAA Compliant, BREEAM Water Credit, cUPC Green Certified, Green Globes Water, IAPMO, LEED Water, Satisfaction LEED Credits, UL Certified, USA, EPA WaterSense Listed)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Graphite (GR), Brushed Stainless (SF).

Downloads

- ↗ Royal ESS Concealed and Exposed Installation Instructions
- ↗ Royal 152_195 ESS TMO (Spanish) Installation Instructions
- ↗ Royal 152_195 ESS TMO Installation Instructions
- ↗ Control Stop Repair and Maintenance Guide
- ↗ Flush Connections Flanges Repair and Maintenance Guide
- ↗ Retrofits Brochure
- ↗ Additional Downloads

Videos

- ▶ ESS Flushometer

Features

- Flush volumes start as low as a pint of water
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.