



Optima® Sensor Faucet

EBF-1150-ITM-GR-0.5GPM-MLM-FCT

Product description

Trim Plate: None, Integrated Thermostatic Mixer, Graphite Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Battery-Powered Basin-Mounted Basin Body Faucet.

Compliances & Certifications



(CEC Compliant, HPD, NYC604.4, TAS)

Code 33153448

Finish



Graphite (GR)

Downloads

- [FLITE-DEC Faucet Installation Instructions.pdf](#)
- [FLITE-DEC Faucet Repair and Maintenance Guide.pdf](#)
- [FLITE-DEC Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Trim Plate: None
- Temperature Mixer: Integrated Thermostatic Mixer (ITM)
- Finish: Graphite (GR)
- Factory Default Timeout: 30s
- Factory Default GPC: 0.25 gpc

Features

- Commercial Grade In-Basin Mounted Faucet
- ADA Compliant
- Machined Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Self-adapting Sensor
- Can withstand up to 150lbs of downward force
- Available only with the FLITE-DEC Integrated Sink System

Recommended specifications

Sloan® FLITE-DEC® Basin Mounted Faucet model ETF-1100. Product to have infrared sensor. Faucet to have Graphite PVD finish. Faucet shall include cast brass body, quick-connect fittings, twist-off/shut-off solenoid assembly, removable battery cartridge and flexible power supply. Faucet must be able to withstand up to 150 lbs of downward force.

Electrical specifications

- Battery Life: 3 years 8,000 cycles/month
- Optional power harvesting significantly extends service life
- Sensor Range: 4" -5" (102-127 mm)
- Timeout Adjustment Setting: 30 Seconds

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EBF-1150 product? [View the general spec sheet with all options.](#)

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet

