

OPTIONS**L Dimension**

- 3 ¾" (95mm) (3-3/4-LDIM)
- 10 ¾" (273mm) (10-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

Metal Index (L)

Control Stop

1" Straight (E)

Compliances & Certifications

BAA Compliant
BABAA Compliant
UPC Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ROYAL 155 shown

DESCRIPTION

Royal® Concealed Manual Service Sink Flushometer

FEATURES

- Standard flush volume is 6.5 gpf /24.6 Lpf
- Flushometers may be ordered with a handle at the front or a push-button actuator
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)