



G2 Sensor Specialty Flushometer

G2 BPW 8005

Product description

G2 Exposed Sensor Specialty Water Closet Bedpan Washer Flushometer.

Finish



Available in Polished Chrome (CP).

Connectivity

 Bluetooth with Sloan Connect App

Downloads

-  [Optima Plus Valve \(SP\) Installation Instructions](#)
-  [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions duplicate](#)
-  [G2 Repair and Maintenance Guide](#)
-  [Control Stop Repair and Maintenance Guide](#)
-  [Flush Connections Flanges Repair and Maintenance Guide](#)
-  [Flushometers Brochure](#)
-  [Additional Downloads](#)

Videos

-  [Sloan - Company Overview](#)

Features

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Battery Specifications

Usage	4-AA Battery Service Life†			
	14.5 yrs	12 yrs	7.2 yrs	6 yrs
per month	500	1,000	3,000	4,000
per day	25	50	150	200

† Service life varies according to actual usage and restroom conditions
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

* Service life varies according to actual usage & restroom conditions
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.