Accessory

# VBF-72-A1

## Product description

VBF-72-A Vacuum Breaker Trap Primer.

## Compliances & Certifications

(IAPMO, UPC Certified)

**Code 3396077**

## Downloads

- Trap Primer Installation Instructions.pdf
- Vacuum Breaker Trap Primer Repair and Maintenance Guide.pdf
- Additional Downloads

## Videos

- Sloan – Company Overview



WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Sloan 10500 Seymour Ave, Franklin Park 800.982.5839 sloan.com

## Features

## Warranty

View Warranty Information

## Notes

All information contained within this document subject to change without notice.

| Model Number | Flush Connection Length "L" | Centerline of Supply to Top of Bowl "A" | Centerline of Supply to Trap Primer Outlet "B" | Critical Line to Trap Primer Outlet "C" |
|---|---|---|---|---|
| 110/111 † | 8½" (216 mm) | 11½" (292 mm) | 7" (178 mm) | 2¼" (57 mm) |
| 113 | 13" (330 mm) | 16" (406 mm) | 11" (280 mm) | 6¼" (159 mm) |
| 115 | 21" (533 mm) | 24" (610 mm) | 11" (280 mm) | 6¼" (159 mm) |
| 116 | 24 (610 mm) | 27" (696 mm) | 11" (280 mm) | 6¼" (159 mm) |

† Check with local codes for approval to use VBF-72-A1 Trap Primer with Model

*When ordering a Sloan Flushometer with a Trap Primer, please specify the "TP" Variation; e.g., Model Number 110 TP.*