Water Closet & Flushometer Combo

WETS-2000.1301-1.28-CP-HW-24V

Product description

1.28 gpf, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, 1” Control Stop, Electrical Override, Hardwired, Sensor-Operated, 24V, ST-2009 Water Closet and ROYAL 111 ESS Flushometer.

Compliances & Certifications

(BAA Compliant, BABAA Compliant, BREEAM Water Credit, EPD, Green Globes Water, HPD, IAPMO, LEED Water, Satisfies LEED Credits, cUPC Certified, EPA WaterSense Listed, WELL Building Standard)

Code 20001301

Downloads

- Royal Exposed Installation Instructions.pdf
- EL 600-A Installation Instructions.pdf
- HET Top Spud Installation Instructions.pdf
- SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf
- Optima ESS Repair and Maintenance Guide.pdf
- Fixture Brochure.pdf
- Additional Downloads

Videos

- Sloan – Company Overview

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Sloan 10500 Seymour Ave, Franklin Park 800.982.5839 sloan.com

Details

- Flush Volume: 1.28 gpf (4.8 lpf)

Features

- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Designed to maximize and complement Sloan flushometers
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Syphon jet flushing achieves 1000g Map Scores when used with Sloan flushometers
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- WaterSense compliant when used with a WaterSense compliant flushometer

Components

- Flushometer: Code 3450049
- Water Closet: Code 2102009

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.


3 ¼" or 5 ¼"
(82 mm or 133 mm)
2 ¾"
(70 mm)
4 ¾"
(121 mm)
SLOAN
OVERRIDE
BUTTON
1" I.P.S.
SUPPLY
(DN 25 mm)
1 1/2"
(38 mm)
19" †
(483 mm)
C/L OF
SUPPLY
11 ½"
(292 mm)
C/L OF
ELECTRICAL
BOX


18-1/2
[470]
1-1/2
[38]
15
[381]
5-1/2
[140]
10-1/2
[267]
14
[356]
7/8 or 2-7/8
[22] [73]
3-1/4 or 5-1/4
[83] [133]
27-5/8 or 29-5/8
[702] [752]
26-3/4
[682]
14
[358]
15
[381]
5-7/8
[149]
10 or 12
[254] [305]