



## Water Closet & Flushometer Combo

**WETS-2701.1101**

### Product description

Standard, ST-2009 Water Closet and ECOS 8111 Flushometer.

### Compliances & Certifications



(ADA Compliant, BREEAM Materials Credit, BREEAM Water Credit, EPD, HPD, LEED Water, Satisfies LEED Credits)

### Code 27011101

#### Downloads

- [HET Top Spud Installation Instructions.pdf](#)
- [ECOS Hardwire Installation Instructions.pdf](#)
- [Additional Downloads](#)

#### Videos

- [Sloan – Company Overview](#)

---

## Details

- Flush Volume: 1.1 gpf (4.2 lpf)

---

## Features

- Dual-flush model automatically initiates a reduced or complete flush based on how long user remains in sensor range, buttons on top of the flush valve enable manual flushing with a standard or reduced flush at restroom visitor's discretion
- Deploys an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay
- High copper, low zinc brass castings for dezincification resistance
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037
- Designed to maximize and complement Sloan flushometers
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Syphonjet flushing achieves 1000g Map Scores when used with Sloan flushometers
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- WaterSense compliant when used with a WaterSense compliant flushometer

---

## Components

- Flushometer: Code 3370460
- Water Closet: Code 2172009

---

## Warranty

[View Warranty Information](#)

---

## Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

