



Vitreous China Service Sink Lavatory

SS-3200

Product description

Vitreous China Service Sink Lavatory.

Compliances & Certifications



(HPD, IAPMO, cUPC Certified)

Code 3873200

()

Downloads

- [SS-3200 Installation](#)
- [Additional Downloads](#)

Videos

- [Sloan - Comparison](#)

Details

Features

Wall mounted clinical service sink.

- Designed to maximize and complement Sloan flushometers
- Exclusive skirted trapway maximizes hygiene and facilitates cleaning
- Thorough blowout flushing action
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- 6.5 gpf (24.6 Lpf)
- White Vitreous China
- Wall mounted, wall China
- Blowout flushing action
- Fully skirted trapway for easy, hygienic cleaning
- 1½" I.P.S. top spud inlet
- Fully glazed trapway
- One (1) stainless steel rim guard (part #SS50) included
- PLUMBING SYSTEM REQUIREMENTS : Minimum flowing pressure: 25 PSI , Maximum static pressure: 80 PSI , Minimum flow rate: 25 GPM

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the SS-3200 product? [View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

