



Accessory

VBF-72-A

Product description

VBF-72-A Vacuum Breaker Trap Primer.

Compliances & Certifications



(IAPMO, UPC Certified)

Code 3396070

Downloads

- [Trap Primer Installation Instructions.pdf](#)
- [Vacuum Breaker Trap Primer Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Features

- 9" VB Flush Connection Assembly

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Model Number	Flush Connection Length "L"	Centerline of Supply to Top of Bowl "A"	Centerline of Supply to Trap Primer Outlet "B"	Critical Line to Trap Primer Outlet "C"
110/111 †	8½" (216 mm)	11½" (292 mm)	7" (178 mm)	2¼" (57 mm)
113	13" (330 mm)	16" (406 mm)	11" (280 mm)	6¼" (159 mm)
115	21" (533 mm)	24" (610 mm)	11" (280 mm)	6¼" (159 mm)
116	24 (610 mm)	27" (696 mm)	11" (280 mm)	6¼" (159 mm)

† Check with local codes for approval to use VBF-72-A1 Trap Primer with Model

When ordering a Sloan Flushometer with a Trap Primer, please specify the "TP" Variation; e.g., Model Number 110 TP.