



Sloan® Soap Dispenser

ESD-1100-BB

Product description

Brushed Brass Finish, 2000 ml, Sloan® Basin-Mounted Top-fill Soap Dispenser.

Code 33461084

Finish



Brushed Brass (BB)

Downloads

- [ESD-1100 Installation Instructions.pdf](#)
- [ESD-1100 Repair and Maintenance Guide.pdf](#)
- [FLITE-DEC Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan Finishes](#)

Details

- Finish: Brushed Brass (BB)
- Power Type: Hardwired
- Height: 1.125" (29mm)
- Width: 2.25" (57mm)
- Sensor Type: IR
- Soap Type: Foam
- Soap Color: Clear
- Soap Scent: Unscented
- Bottle Size: 2000 ml

Features

- Mounts to basin wall
- 2.85 Gallon Reservoir, Top-fill closed soap system
- Can withstand up to 150 lbs of downward force applied to front of spout
- Top-fill refill quick connect
- Soap Reservoir supplies one soap dispenser
- Low Soap Level Indicator
- All electronics sealed
- Double infrared sensors with automatic setting feature
- Foaming Soap Refill (not included)
- Available only with the FLITE-DEC Integrated Sink System
- Brushed brass finish

Recommended specifications

Sloan ESD-1100 Top-Fill FLITE-DEC Soap Dispenser. Must include 2.85 gallon Reservoir. Soap Dispenser to have Brushed Brass finish. Must be supplied with 2 bottles of 2000ml Purell(R) REDIFOAM soap. Must be a closed soap system to eliminate the risk of overflowing and contamination of the reservoir. Soap Dispenser must be able to withstand up to 150lbs. of downward force.

Soap Refills

- ESD-347 (2000 ml)

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

