



PWT™ Accessory

MCR-4004

Product description

PWT System 4-I/O Controller.

Compliances & Certifications



(BAA Compliant)

Code 0375280

Downloads

- [MCR-4004_4014_8002_8012.pdf](#)
- [Programmed Water Technologies \(PWT\) Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Features

- Four input/output field-programmable controller to control lavatories, water closets, showers or combination fixtures
- 24 VAC — 50/60 Hz operating voltage
- Operating temperature: 0°C to 85°C
- Input (push button) voltage: 5 VDC
- Output (solenoid) voltage: 24 VAC
- PC Board conformably coated to resist moisture and dust
- RJ-11, 6 position, 4 pin connections for push buttons and solenoids
- Diagnostic LED at each input and output connection
- Lock-out indicator
- Potentiometer on PC Board allows for adjustment of run-times or lock-out times depending on program variation
- Can be installed up to 200 feet away from 24 VAC power supply
- Includes mounting hardware
- Optional LED Button for Water Closet I/O PROGRAM

CONFIGURATIONS

- All Closet, with adjustable lock out time up to four water closets
- All Shower, with adjustable default “run time” up to four showers
- All Lavatories, with adjustable default “run time” up to four lavatories
- Combination fixture controls a hot/cold water lavatory, a water closet and a shower. Adjustable default “run time” and “lock-out times”. Factory set for 1-hour lock-out time.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

