

OPTIONS**Flush Volume**

3.5 gpf (13.2 Lpf) (3.5)

1.6 gpf (6.0 Lpf) (1.6)

Water Efficiency

Water Saver

Low Consumption

L Dimension

10 ¾" (273mm) (10-3/4-LDIM)

12 ¾" (324mm) (12-3/4-LDIM)

7 ¾" (197mm) (7-3/4-LDIM)

5 ¾" (146mm) (5-3/4-LDIM)

6 ¾" (171mm) (6-3/4-LDIM)

8 ¾" (222mm) (8-3/4-LDIM)

9 ¾" (248mm) (9-3/4-LDIM)

11 ¾" (298mm) (11-3/4-LDIM)

13 ¾" (349mm) (13-3/4-LDIM)

14 ¾" (375mm) (14-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Handle

Front of Valve (H)

Metal Oscillating (J)

Push Button

Less (L/C9A)

3" Metal Oscillating (L3)

Control Stop

1" Straight (E)

Compliances & Certifications

BAA Compliant

BABAA Compliant

Made in the USA

UPC Certified

cUPC Certified

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ROYAL 601 shown

DESCRIPTION

Royal® Concealed Manual Specialty Water Closet Flushometer

FEATURES

- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Concealed Flushometer Installation Instructions for Stainless Steel Fixtures](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)