

OPTIONS

Flush Volume

- 1.0 gpf (3.8 Lpf) (1.0)
- 1.5 gpf (5.7 Lpf) (1.5)
- 0.5 gpf (1.9 Lpf) (0.5)
- 3.5 gpf (13.2 Lpf) (3.5)
- 0.125 gpf (0.5 Lpf) (0.125)

Water Efficiency

- Low Consumption
- Water Saver
- High Efficiency

L Dimension

- 10 ¾" (273mm) (10-3/4-LDIM)
- 6 ¾" (171mm) (6-3/4-LDIM)
- 8 ¾" (222mm) (8-3/4-LDIM)
- 12 ¾" (324mm) (12-3/4-LDIM)
- 3 ¾" (95mm) (3-3/4-LDIM)
- 5 ¾" (146mm) (5-3/4-LDIM)
- 7 ¾" (197mm) (7-3/4-LDIM)
- 11 ¾" (298mm) (11-3/4-LDIM)
- 14 ¾" (375mm) (14-3/4-LDIM)
- 9 ¾" (248mm) (9-3/4-LDIM)

Wall Box

- Standard (not included, order separately)

Handle

- Front of Valve (H)
- Metal Oscillating (J)

Push Button

- 3" Metal Oscillating (L3)
- Less (L/C9A)

Control Stop

- 1" Straight (E)

Inlet

- Back of Valve (B)

Compliances & Certifications

- BAA Compliant
- BABAA Compliant
- UPC Certified
- Made in the USA
- cUPC Certified
- BREEAM Water Credit
- Green Globes Water Credit
- LEED V4 Water Efficiency Credit



Image for a standard ROYAL 613 shown

DESCRIPTION

Royal® Concealed Manual Specialty Urinal PWT Flushometer

FEATURES

- Royal®, Regal® and Sloan® Prison Flushometers feature all the performance benefits of standard concealed, diaphragm model Flushometers with added durability to withstand rough environments
- Flush volumes as low as 0.5 gpf/1.9 Lpf meet water-efficiency goals
- Push button-activated Flushometers intended for use with stainless-steel urinal fixtures from various manufacturers
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Concealed Flushometer Installation Instructions for Stainless Steel Fixtures](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Royal Manual Diaphragm Flushometer Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Satisfies LEED Credits
WaterSense Listed

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.