



Urinal & Flushometer Combo

WEUS-7005.1310

Product description

Standard, SU-7009 Urinal and ROYAL 186 ESS Flushometer.

Compliances & Certifications



(ADA Compliant*, BAA Compliant, EPD, HPD, IAPMO, Satisfies LEED Credits, EPA WaterSense Listed, WELL Building Standard)

Code 70051310

Downloads

- [Small Spud Urinal Installation Instructions.pdf](#)
- [Royal ESS TMO Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Optima ESS TMO Concealed Repair and Maintenance Guide.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Details

- Flush Volume: 0.5 gpf (1.9 lpf)

Features

- Complete urinal system including Royal 186 ESS flushometer designed to maximize performance
- Thorough washdown flushing action
- Durable, hygienic vitreous china construction
- Vandal resistant stainless steel strainer included
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- Water Sense listed by EPA that qualifies for most rebate programs
- Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

Components



- Flushometer: Code 3452642
- Urinal: Code 1107009

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice. @AttributePlain:*Compliant with ADA accessibility requirements when installed according to ADA standards.



NOTE: ADA urinal rim height requirements allow all heights 17" and below. Sloan strongly recommends roughing in the drain to achieve a 16 1/2" rim height or less to ensure compliance.