

OPTIONS

Flush Volume

1.28 gpf (4.8 Lpf) (1.28)

Finish

Polished Chrome (CP)

Activation

Sensor Specialty

Valve

Diaphragm

Bypass

Dual-Filtered Fixed Bypass Diaphragm

Fixture Type

Water Closet

Installation

Exposed

Specialty

Bedpan Washer

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

BREEAM Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

UL Certified

UPC Certified

WaterSense Listed

cUPC Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

Sloan® Exposed Sensor Specialty Hardwired Water Closet Bedpan Washer Flushometer

FEATURES

- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- BPW ESS Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Optima ESS Repair and Maintenance Guide
- Slimline Bedpan Washer Repair and Maintenance Guide
- Additional Downloads

VIDEOS



ESS Flushometer

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com