



## Sloan® Sensor Flushometer

SLOAN 195 ESS-ES-SM-1.5-RB-HW-24V

### Product description

1.5 gpf, Rough Brass Finish, Fixture Connection Rear Spud, Single Flush, 2"-10.75" L Dimension, Hardwired, Sensor-Operated with Modular Plug, 24V, Sloan® Concealed Sensor Hardwired Urinal Flushometer.

### Compliances & Certifications



(ADA Compliant\*, BAA Compliant, BABAA Compliant, IAPMO, UL Certified (US), cUPC Certified)

### Code 3783203

#### Finish



Rough Brass (RB)

#### Downloads

- [Sloan Concealed Installation Instructions.pdf](#)
- [Sloan 152\\_195 ESS TMO Installation Instructions.pdf](#)
- [Sloan 152\\_140\\_153\\_195 ESS TMO SWB Installation Instructions.pdf](#)
- [Sloan:Regal ESS Repair and Maintenance Guide.pdf](#)
- [Optima ESS Repair and Maintenance Guide.pdf](#)
- [Retrofits Brochure.pdf](#)
- [Additional Downloads](#)

#### Videos

- [ESS Flushometer](#)

## Details

- Flush Volume: 1.5 gpf (5.7 lpf)
- Finish: Rough Brass (RB)
- Power Type: Hardwired (HW)
- Valve: Diaphragm
- Valve Body Material: Semi-red Brass
- Fixture Type: Urinal
- Fixture Connection: Rear Spud
- Rough-in Dimension: 13.5" (343mm)
- Spud Coupling: 0.75" (19mm)
- Supply Pipe: 0.75" (19mm)
- L Dimension: 2"-10.75" (51-273mm)
- Voltage: 24V (24V)

## Features

- Flush volumes start as low as 1.0 gpf/3.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents urinal from exceeding intended flush volume
- Low-consumption flush accuracy also enhances water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

## Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

## Electrical specifications

- Arming Delay: 8 seconds
- Sensor Range: 0"-36" (0 - 914mm)
- Solenoid Operator: 24 VAC
- Transformers (Specify Separately):
  - EL-154/0345154
  - EL-342/0345999

## Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

## Warranty

[View Warranty Information](#)

## Notes

All information contained within this document subject to change without notice.

\*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the SLOAN 195 ESS product?

[View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

