



Optima® Sensor Faucet

EAF-250-BAT-SF-0.35GPM-MLM-IQ-FCT

Product description

Battery Power Supply, Mixer Not Included, Brushed Stainless Finish, 0.35 gpm, Multi-Laminar Spray, Infrared Sensor, Optima® Battery-Powered Deck-Mounted Mid Body Faucet.

Compliances & Certifications



(ASME A112.18.1 Compliant, CalGreen Compliant, CEC Compliant, EPD, GPC 0.25 or less, HPD, LEED Water, NSF-61/CAN-61, NYC604.4, Satisfies LEED Credits, TAS, WELL Building Standard)

Code 33351351

Finish

 Brushed Stainless (SF)

Downloads

-  EAF 200_225_250_275 Installation Instructions.pdf
-  EAF 200_225_250_275 (SP) Installation Instructions.pdf
-  Faucet Spray Heads Maintenance Guide.pdf
-  Faucet and Soap Dispenser Brochure.pdf
-  Additional Downloads

Videos

-  PVD Special Finishes

Details

- Flow Rate: 0.35 gpm (1.3 Lpm) (0.35GPM)
- Spray Type: Multi-Laminar (MLM)
- Sensor Type: Infrared
- Mounting Type: Single Hole
- Power Supply: Battery (BAT)
- Temperature Mixer: Mixer Not Included
- Finish: Brushed Stainless (SF)
- Factory Default Timeout: 30s
- Factory Default GPC: 0.083 gpc

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- Double Infrared Sensors with Automatic Setting Feature and Microprocessor
- Automatic Self-adapting Sensor Technology
- Low Battery Indicator
- Magnetic Solenoid Valve
- Water Supply Connection with Flexible High-pressure Hose and Strainer
- 6 volt Lithium CR-P2 Commercial Battery included
- Appropriate Mounting Hardware included
- 3 year limited warranty
- Brushed Stainless Finish
- 0.35GPM flow pattern Rate with multi-laminar flow pattern
- Battery powered with 2 CRP-2 Lithium batteries included

Electrical specifications

- Battery Life: 3 years 8,000 cycles/month
- Optional power harvesting significantly extends service life
- Sensor Range: 4"-5" (102-127 mm)
- Timeout Adjustment Setting: 10 Seconds

Warranty

[View Warranty Information](#)



Notes

All information contained within this document subject to change without notice.

Looking for other variations of the EAF-250 product? [View the general spec sheet with all options.](#)

[Find a matching soap dispenser](#) for this faucet.


[Find a compatible sink](#) for this faucet



When the EAF faucet is installed on a sink that has three (3) hole punchings, a Trim Plate should be used. **Trim Plates must be specified and ordered separately:**

ETF-312-A
Trim Plate for 4" (102 mm)
Centerset Sink

ETF-510-A
Trim Plate for 8" (204 mm)
Centerset Sink



Optional EAF-35-A Faucet Extension Kit

