

OPTIONS**Power Supply**

Box Transformer (BOX)

Plug Adapter (PLG)

Flow Rate

0.5 gpm (1.9 Lpm) (0.5GPM)

0.35 gpm (1.3 Lpm) (0.35GPM)

Trim Plate

4" (102mm) (4)

8" (203mm) (8)

Mixer

Mixer Not Included

Below Deck Manual Mixing Valve (BDM)

Below Deck Thermostatic Mixing Valve (BDT)

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.[Find a compatible sink](#) for this faucet.

Image for a standard ETF-420 SMT shown

DESCRIPTION

Optima® Hardwired-Powered Deck-Mounted Mid Body IoT

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor
- Faucet operates normally when not connected to the SC Argus Pro system
- Automatic two-way communication with IOT cloud-based system
- Remote management and monitoring of faucet
- Comprehensive view of product information with image and location information
- Collects and sends information on activations, water usage, battery power level
- Remote settings changes, line flush management and faucet set up
- Sends notification and alarms on battery level, diagnostics, communication issues

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

- 110V or 230V/6VDC plug adapter

DOWNLOADS

- [Optima Smart Faucet Below Deck Installation Instructions](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [Optima EBF-425 / ETF-420 Repair & Maintenance Guide and Parts Breakdown](#)
- [Trim Plate Guide](#)
- [Additional Downloads](#)

VIDEOS

-  [Sloan Optima Below Deck Faucet](#)
-  [PVD Special Finishes](#)
-  [SC Argus™ Pro](#)