



Sloan Optima Air® Hand Dryer

EHD-702-BN

Product description

EHD-702, 208/277V, Sloan Optima Air® Sensor-Operated Wall-Mounted - ADA Hand Dryer.

Compliances & Certifications



(BAA Compliant, UL Certified (US and Canada))

Code 3366131

Finish



Brushed Nickel (BN)

Downloads

-  [OPTIMA AIR HAND DRYER EHD-700 SERIES.pdf](#)
-  [Sloan Hand Dryers Brochure.pdf](#)
-  [Additional Downloads](#)

Videos

-  [Sloan – Company Overview](#)

Details

- Finish: Brushed Nickel (BN)
- Voltage: 208/277V
- Amperage: 3.6A-4.0A
- Mounting: Wall-Mounted - ADA
- Power Type: Hardwired
- Depth: 13.9375" (102mm)
- Height: 13.9375" (354mm)
- Width: 9.156" (233mm)

Features

- Hygienic hand drying solution, 35-second lockout feature if hands are not removed
- 95% cost savings vs. paper towels
- Electric Specifications: 208-277V 5.6 – 6.2A
- Meets ADA requirements without the need of a recess kit
- Adjustable speed and sound (High-Low), Adjustable Heat (High-Low-Off)
- Vandal resistant cover design, Virtually maintenance free
- Available in Polished White and Brushed Nickel
- Weight: 8-10 lbs.
- Quantity Recommendations: 1 dryer for every 2 sink stations is sufficient for most applications. For high traffic applications we suggest 1 dryer per sink station
- Suggested Mounting Heights for Ideal Performance (from floor to bottom of dryer): Men: 45" (114 cm), Women: 43" (109 cm), Teenagers: 41" (104 cm), Children: 35" (89 cm), ADA: 37" (94 cm).
Note: When mounting for any user ensure that it is mounted below the 48" ADA Maximum
- Externally visible Red LED light that flashes error codes to assist in troubleshooting and identify if filter has been clogged
- Air temperature of up to 141°F (61°C) at a 72°F (22°C) ambient room temperature at the hands (4 inches [102 mm] below air outlet)

Recommended specifications

EHD-702 Brushed Nickel Finish, 208V

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

