



Royal® Manual Specialty Flushometer

ROYAL BPW 1000-1.6-CP-SG-2-OFST

Product description

1.6 gpf, Polished Chrome Finish, Fixture Connection Top Spud, Single Flush, Saniguard® Handle, 2" Offset, F190 Outlet Tube, Royal® Exposed Manual Specialty Service Sink Bedpan Washer Flushometer.

Compliances & Certifications



(ADA Compliant*, BAA Compliant, BABAA Compliant, IAPMO, UPC Certified)

Code 3919794

Finish

 Polished Chrome (CP)

Downloads

-  Slimline Royal_Regal XL Exposed Installation Instructions.pdf
-  Slimline Bedpan Washer Repair and Maintenance Guide.pdf
-  Retrofits Brochure.pdf
-  Additional Downloads

Videos

-  Sloan - Company Overview

Product Information

Details

- Flush Volume: 1.6 gpf (6.0 lpf)
- Finish: Polished Chrome (CP)
- Valve: Diaphragm
- Valve Body Material: Semi-red Brass
- Fixture Type: Service Sink
- Fixture Connection: Top Spud
- Rough-in Dimension: 34.375" (873mm)
- Spud Coupling: 1.5" (38mm)
- Supply Pipe: 1" (25mm)
- Handle Type: Saniguard® (SG)
- Offset: 2" (51mm) (2-OFST)
- Outlet Tube: F190

Features

- Exposed water closet, diaphragm model Flushometer is intended for floor-mounted or wall-hung top spud bowls
- Operates by means of a metal oscillating, non-hold-open handle with a triple seal handle packing to ensure water conservation
- Presents a leaner, more aesthetic installation, reducing possible bacteria growth on hidden and hard-to-reach surfaces found on other bedpan washer units
- Eliminates the need for unsanitary hose sprays, as well as the additional housekeeping that hoses require and the potential for patient slippage
- Valve body, stop body, diverter body and diverter pivot made from brass casting using semi-red brass for durability and long life
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

ROYAL BPW 1000-1.6-CP-SG-2-OFST

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the ROYAL BPW 1000 product?

[View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

