

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6)

6.5 gpf (24.6 Lpf) (6.5)

3.5 gpf (13.2 Lpf) (3.5)

1.28 gpf (4.8 Lpf) (1.28)

Finish

Polished Chrome (CP)

Activation

Manual Specialty

Valve

Diaphragm

Water Efficiency

Low Consumption

Water Saver

High Efficiency

Fixture Type

Service Sink

Fixture Connection

Dug2 aoT

Installation

Exposed

Handle

Saniguard®

Front of Valve (H)

Control Stop

Adjustable Ground Joint (ADJ/GJ)

Less (L/STOP)

Vacuum Breaker

Offset (O)

V600A

Offset

2" (51mm) (2-OFST)

1" (25mm) (1-OFST)

1 ½" (38mm) (1-1/2-OFST)

Outlet Tube

F190

Trap Primer (TP)

F182



DESCRIPTION

Royal® Exposed Manual Specialty Service Sink Bedpan Washer Flushometer

FEATURES

- Exposed water closet, diaphragm model Flushometer is intended for floor-mounted or wall-hung top spud bowls
- Operates by means of a metal oscillating, non-hold-open handle with a triple seal handle packing to ensure water conservation
- Presents a leaner, more aesthetic installation, reducing possible bacteria growth on hidden and hard-to-reach surfaces found on other bedpan washer units
- Eliminates the need for unsanitary hose sprays, as well as the additional housekeeping that hoses require and the potential for patient slippage
- Valve body, stop body, diverter body and diverter pivot made from brass casting using semi-red brass for durability and long life
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- Slimline Royal/Regal XL Exposed Installation Instructions
- Slimline Bedpan Washer Repair and Maintenance Guide
- Additional Downloads



Fitting

F31AA

Specialty

Bedpan Washer

Compliances & Certifications

BAA Compliant
UPC Certified
BABAA Compliant
cUPC Certified
BREEAM Water Credit
Green Globes Water Credit

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.