

OPTIONS

Flush Volume

- 1.28/1.1 gpf (4.8/4.2 Lpf) (1.28/1.1)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)

Finish

- Polished Chrome (CP)
- Graphite (GR)

Power Type

- Hardwired (HW)

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- High Efficiency

Bypass

- Dual-Filtered Bypass

Fixture Type

- Water Closet

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Electrical

Control Stop

- 1"

Inlet

- 1"

Outlet Tube

- Trap Primer (TP)

Special Features

- Carbon Offset (CO)

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BABAA Compliant
- BREEAM Water Credit



Image for a standard ECOS 111 shown

DESCRIPTION

ECOS® Exposed Sensor Hardwired Water Closet Flushometer

FEATURES

- Automatically initiates a 1.1 gpf or 1.6 gpf flush based on how long the user remains in sensor range
- Buttons on top of the flush valve enable manual flushing with a full or reduced flush at restroom visitor's discretion
- Employs an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay
- High copper, low zinc brass castings for dezincification resistance
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [ECOS HW Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

Green Globes Water Credit
cUPC Certified
cUPC Green Certified
UL Certified
UPC Certified
WaterSense Listed

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.