



BASYS® Sensor Faucet

EFX-377

Product description

BASYS® Solar-Powered Deck-Mounted Low Body Guided Handwashing Display Faucet.

Compliances & Certifications



(ASME A112.18.1 Compliant, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, EPD, GPC 0.25 or less, HPD, LEED Water, NYC604.4, Satisfies LEED Credits, TAS, WELL Building Standard)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Polished Chrome (CP).

Downloads

- [EFX 3Xx_6Xx Active IR Installation Instructions](#)
- [EFX 3Xx_6Xx Active IR \(SP\) Installation Instructions](#)
- [Trim Plate Guide](#)
- [IR FAQs Repair and Maintenance Guide](#)
- [Sloan BASYS Brochure](#)
- [Additional Downloads](#)

Videos

- [BASYS® Guided Handwashing Faucets](#)
- [BASYS® Faucet Installation and Features](#)
- [Sloan Connect App®](#)

Features

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Die-Cast Metal Hand Washing Faucet with the following features:

- One tool service
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-67
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power-up mode
- Flexible, high pressure supply hose, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four (4) "AA" alkaline batteries
- Double infrared sensors with automatic setting feature
- Single hole installation (pedestal)
- Includes all mounting hardware
- 3 year limited warranty

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Compatible products



ESD-500

[View product >](#)