



Water Closet & Flushometer Combo

WETS-2452.3002

Product description

ST-2459 Water Closet and REGAL 111 SFM Flushometer.

Compliances & Certifications



(BAA Compliant, BABAA Compliant)

Code 24523002

Downloads

- [HET Wall Hung Water Closet Installation Instructions.pdf](#)
- [Regal XL Exposed Installation Instructions.pdf](#)
- [EBV-500_550-A Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Regal Flushometers Repair and Maintenance Guide.pdf](#)
- [EBV500-EBV550 Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flush Volume: 1.6 gpf (6 lpf)

Features

- Durable, hygienic vitreous china construction with elongated rim and hardwired sensor operated side mount flushometer
- Adjustable tailpiece with control stop plug maintains the integrity of the product
 - Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
 - Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
 - Valve shall be in compliance to the applicable sections of ASSE 1037
 - Maximum static load rating of 1,000 lbs when installed on an appropriate wall carrier support system (not recommended for bariatric use)
 - Syphon jet flushing achieves 1000g Map Scores when used with Sloan flushometers
 - IAPMO certified to meet or exceed ASME A112.19.2 standards
 - Meets ADA guidelines and ANSI A117.1 requirements when installed accordingly

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Components

- Flushometer: Code 3980096
- Water Closet: Code 2102459

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

