



Variation Not Shown: Metal Index Push Button

Royal® Manual Flushometer

ROYAL 197-1.0-RB-WB-8-3/4-LDIM-L

Product description

1.0 gpf, Rough Brass Finish, Fixture Connection Top Spud, Single Flush, 8.75" L Dimension, Metal Index Push Button, Standard size (WB-1-A wall box not included- order separately) Wall Box, Royal® Concealed Manual Urinal Flushometer.

Compliances & Certifications



(BAA Compliant, IAPMO, Made in the USA, cUPC Certified)

Code 3913299

Finish



Downloads

- [Sloan Concealed Installation Instructions.pdf](#)
- [Control Stop Repair and Maintenance Guide.pdf](#)
- [Flush Connections Flanges Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Product Information

Details

- Flush Volume: 1.0 gpf (3.8 lpf)
 - Finish: Rough Brass (RB)
 - Valve: Diaphragm
 - Valve Body Material: Semi-red Brass
 - Fixture Type: Urinal
 - Fixture Connection: Top Spud
 - Rough-in Dimension: 13.5" (343mm)
 - Spud Coupling: 0.75" (19mm)
 - Supply Pipe: 0.75" (19mm)
 - L Dimension: 8.75" (222mm) (8-3/4-LDIM)
 - Wall Box: Standard size (WB-1-A wall box not included- order separately) (undefined)
 - Push Button: Metal Index (L)
-

Features

- Flush volumes start as low as a pint of water
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

ROYAL 197-1.0-RB-WB-8-3/4-LDIM-L

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Looking for other variations of the ROYAL 197 product? [View the general spec sheet with all options.](#)

[Find a compatible urinal](#) for this flushometer.

[Find a compatible water closet](#) for this flushometer.

