



### Sloan® Sensor Faucet

SF-2800-PLG-TEE-CP-0.5GPM-MLM-FCT

## **Product description**

Plug Adapter Power Supply, Back-Check Tee, Polished Chrome Finish, 0.5 gpm, Multi-Laminar Spray, Infrared Sensor, Sloan® Hardwired-Powered Wall-Mounted Wall Body Faucet.

## Compliances & Certifications















(ADA Compliant, ASME A112.18.1 Compliant, CalGreen Compliant, CEC Compliant, GPC 0.25 or less, IAPMO, NSF-61/CAN-61, NYC604.4, Proposition 65, TAS, UPC Low Lead Certified, WELL Building Standard)

### Code 33621018

### **Finish**



Polished Chrome (CP)

## **Downloads**

- SF Series Installation Instructions.pdf
- SF Series (FR) Installation Instructions.pdf
- SF Series (SP) Installation Instructions.pdf
- SF 2800:2850 Repair and Maintenance Guide\_0.pdf
- Faucet and Soap Dispenser Brochure.pdf
- Faucets Brochure (Spanish).pdf
- Additional Downloads

## Videos

Sloan - Company Overview

# **Product Information**

# SF-2800-PLG-TEE-CP-0.5GPM-MLM-FCT

#### **Details**

• Flow Rate: 0.5 gpm (1.9 Lpm) (0.5GPM)

· Spray Type: Multi-Laminar (MLM)

Spout Type: PedestalSensor Type: Infrared

· Mounting Type: Single Hole

· Power Supply: Plug Adapter (PLG)

Temperature Mixer: Back-Check Tee (TEE)

• Finish: Polished Chrome (CP)

• Factory Default Timeout: 30s

• Factory Default GPC: 0.25 gpc

### **Features**

Commercial Grade, ADA Compliant, Electronic, Sensor-Activated, Brass Wall-Mounted Hand Washing Faucet with the following features:

- · Adjustable Infrared Sensor Range
- 36" (914 mm) Long Sensor Cable
- 24" (610 mm) Long Flex Hose
- · Filtered Solenoid Valve with serviceable Strainer Filter
- · Includes Four (4) AA-size Batteries
- · Includes appropriate Mounting Hardware
- 1 Year limited warranty
- · Chrome Plated Finish
- · 0.5GPM Flow Rate with multi-laminar flow
- · Includes Plug Adapter

### Recommended specifications

Faucet shall include cast brass body, plug adapter, Alkaline batteries for backup power and 0.5qpm multilaminar spray head.

### **Electrical specifications**

- · Battery Life: 2 years 8,000 cycles/month
- · Timeout Adjustment Setting: 30 Seconds

### Warranty

View Warranty Information

#### **Notes**

All information contained within this document subject to change without notice.

Looking for other variations of the SF-2800 product? View the general spec sheet with all options.

Find a matching soap dispenser for this faucet.

Find a compatible sink for this faucet







