

OPTIONS**Power Type**

Battery
Turbine

Body Type

Gooseneck

Mounting

Wall

Power Supply

Battery (BAT)
Battery + Turbine (TUR)

Sensor Type

Infrared

Flow Rate

1.5 gpm (5.7 Lpm) (1.5GPM)
2.2 gpm (8.3 Lpm) (2.2GPM)
0.35 gpm (1.3 Lpm) (0.35GPM)
1.0 gpm (3.8 Lpm) (1.0GPM)

Spray Type

Laminar (LAM)
Shower Head (SHR)
Multi-Laminar (MLM)

Spout Type

Surgical Bend (S)

Finish

Polished Chrome (CP)

Control Access

Below Deck

Mixer

Back-Check Tee (TEE)
Below Deck Thermostatic Mixing Valve (BDT)
Below Deck Manual Mixing Valve (BDM)

Compliances & Certifications

ADA Compliant
ASME A112.18.1 Compliant
EPD
HPD
IAPMO
NSF-61
Proposition 65
TAS



Image for a standard EBF-550 shown

DESCRIPTION

Optima® Battery or Turbine-Powered Wall-Mounted Gooseneck Body

FEATURES

- Commercial Grade Faucet
- ADA Compliant
- Cast Brass Spout
- Quick Connect Fittings
- Integrated Water Shut-off
- Wireless Settings Adjustment
- On-demand or Metered activation
- Hygienic Line Flush
- Water Usage and Battery Strength Reporting
- Self-adapting Sensor

SMART FAUCET ADDITIONAL OPTIONS

- 24VAC plug adapter, power harness assembly or box mount power supply
- Multi-unit gang adapter kit
- 110V or 230V/6VDC plug adapter
- Special PVD finishes available Brushed Stainless, Brushed Nickel, Polished Brass and Matte Black

DOWNLOADS

- [Optima Smart Faucet Below Deck Installation Instructions](#)
- [Faucet Spray Heads Repair and Maintenance Guide](#)
- [ETF-500/500-S and EBF-550/550-S Below Deck Repair and Maintenance Guide](#)
- [Additional Downloads](#)

UPC Certified
UPC Low Lead Compliant

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

[Find a matching soap dispenser](#) for this faucet.

[Find a compatible sink](#) for this faucet.

VIDEOS

-  [Sloan Connect App®](#)
-  [Sloan Optima Below Deck Faucet](#)