



Act-O-Matic® Showerhead

AC-460-1.8GPM-CP

Product description

Polished Chrome Finish, Act-O-Matic® Institutional Behind the Wall Installation Showerhead.

Compliances & Certifications



(ASME A112.18.1 Compliant, BAA Compliant, BABAA Compliant, BREEAM Water Credit, CEC Compliant, Green Globes Water, IAPMO, IAPMO listed ASME, LEED Water, Satisfies LEED Credits, cUPC Certified, EPA WaterSense Listed)

Code 4024631

Finish

 Polished Chrome (CP)

Downloads

- [AC 450_460 Installation Instructions.pdf](#)
- [Showerhead Parts and Accessories Repair and Maintenance Guide.pdf](#)
- [Programmed Water Technologies \(PWT\) Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Finish: Polished Chrome (CP)
- Flow Rate: 1.8 gpm (6.8Lpm) (1.8GPM)
- Self Cleaning: Yes

Features

- Institutional Style Shower Head
- Designed for secure, in-wall installation (behind the wall access required for installation)
- Spring-loaded, self-cleaning spray disk prevents particle clogging and reduces maintenance
- “Cone within a cone” spray pattern for total body coverage
- All brass construction
- 1/2” IPS inlet
- Fast drain feature to prevent residual slow dripping
- Shower Head shall be in conformance to all requirements of ANSI/ ASME Standard A112.18.1M, CSA B-125 and the United States Federal Energy Policy Act.
- Polished Chrome Finish
- Adjustable spray angle with pressure compensating 1.8 gpm (6.8 Lpm) flow control
-
- Mounting Plate with Vandal Resistant Mounting Screws
-

Recommended specifications

Sloan Act-O-Matic Institutional Showerhead model no. AC-460 1.8 gpm. Vandal Resistant and Chrome Plated.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

