



Sloan® Manual Flushometer

SLOAN 154-1.28-RB-WB-10-3/4-LDIM

Product description

1.28 gpf, Dual-Filtered Fixed Bypass Diaphragm, Rough Brass Finish, Fixture Connection Rear Spud, Single Flush, 10.75" L Dimension, Standard size (WB-1-A wall box not included- order separately) Wall Box, Sloan® Concealed Manual Water Closet Flushometer.

Compliances & Certifications



(BAA Compliant, BREEAM Water Credit, cUPC Green Certified, Green Globes Water, IAPMO, LEED Water, Made in the USA, Satisfies LEED Credits, EPA WaterSense Listed)

Code 3781733

Finish

 Rough Brass (RB)

Downloads

- [Sloan Concealed Installation Instructions.pdf](#)
- [Control Stop Repair and Maintenance Guide.pdf](#)
- [Flush Connections Flanges Repair and Maintenance Guide.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Product Information

Details

- Flush Volume: 1.28 gpf (4.8 lpf)
 - Finish: Rough Brass (RB)
 - Valve: Diaphragm
 - Bypass: Dual-Filtered Fixed Bypass Diaphragm
 - Valve Body Material: Semi-red Brass
 - Fixture Type: Water Closet
 - Fixture Connection: Rear Spud
 - Rough-in Dimension: 24" (610mm)
 - Spud Coupling: 1.5" (38mm)
 - Supply Pipe: 1" (25mm)
 - L Dimension: 10.75" (273mm) (10-3/4-LDIM)
 - Wall Box: Standard size (WB-1-A wall box not included- order separately) (undefined)
-

Features

- High chloramine resistant PERMEX®synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

SLOAN 154-1.28-RB-WB-10-3/4-LDIM

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

WaterSense compliant when used with a 1.28 gpf (4.8 lpf) WaterSense fixture.

Looking for other variations of the SLOAN 154 product? [View the general spec sheet with all options.](#)
[Find a compatible urinal](#) for this flushometer.
[Find a compatible water closet](#) for this flushometer.

