



## Sloan® Sensor Flushometer

### SLOAN 180 ESS

#### Product description

Sloan® Exposed Sensor Hardwired Urinal Flushometer.

#### Compliances & Certifications



(ADA Compliant, BAA Compliant, IAPMO, UL Certified, USA, UPC Certified)

Listed compliances and certifications may vary based on product variation.

#### Finish



Available in Polished Chrome (CP).

#### Downloads

- [Sloan\\_Regal Concealed and Exposed Sensor Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Additional Downloads](#)

#### Videos

- [ESS Flushometer](#)

---

## Features

- Flush volumes start as low as 1.0 gpf/3.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents urinal from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece to accommodate different height requirements
- High chloramine resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

---

## Warranty

[View Warranty Information](#)

---

## Notes

All information contained within this document subject to change without notice.