

OPTIONS

Flush Volume

1.6 gpf (6.0 Lpf) (1.6) 3.5 gpf (13.2 Lpf) (3.5)

Water Efficiency

Low Consumption Water Saver

L Dimension

3 ¾" (95mm) (3-3/4-LDIM) 2"-10 ¾" (51-273mm) 4 ¾" (121mm) (4-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

3" Metal Oscillating (L3)

Voltage

24V

Compliances & Certifications

BAA Compliant BABAA Compliant UPC Certified cUPC Certified ADA Compliant UL Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

Royal® Concealed Manual Specialty Water Closet Bedpan Washer Flushometer

FEATURES

- Concealed water closet, diaphragm model Flushometer is intended for floor-mounted or wall-hung top spud bowls
- Operates by means of a metal oscillating, non-hold-open handle with a triple seal handle packing to ensure water conservation
- Presents a leaner, more aesthetic installation, reducing possible bacteria growth on hidden and hard-to-reach surfaces found on other bedpan washer units
- Eliminates the need for unsanitary hose sprays, as well as the additional housekeeping that hoses require and the potential for patient slippage
- Valve body, stop body, diverter body and diverter pivot made from brass casting using semi-red brass for durability and long life
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- BPW Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Royal Manual Diaphragm Flushometer Repair and

Sloan 10500 Seymour Ave, Franklin Park, IL 60131



Maintenance Guide

- Slimline Bedpan Washer Repair and Maintenance Guide
- Additional Downloads

Sloan 10500 Seymour Ave, Franklin Park, IL 60131 Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com