

OPTIONS**Flush Volume**

3.5 gpf (13.2 Lpf) (3.5)

1.6 gpf (6.0 Lpf) (1.6)

Water Efficiency

Water Saver

Low Consumption

L Dimension

10 ¾" (273mm) (10-3/4-LDIM)

4 ¾" (121mm) (4-3/4-LDIM)

6 ¾" (171mm) (6-3/4-LDIM)

3 ¾" (95mm) (3-3/4-LDIM)

11 ¾" (298mm) (11-3/4-LDIM)

7 ¾" (197mm) (7-3/4-LDIM)

12 ¾" (324mm) (12-3/4-LDIM)

13 ¾" (349mm) (13-3/4-LDIM)

2 ¾" (70mm) (2-3/4-LDIM)

5 ¾" (146mm) (5-3/4-LDIM)

Wall Box

Standard (not included, order separately)

Push Button

3" Metal Oscillating (L3)

Metal Index (L)

Control Stop

Ground Joint (GJ)

1" Straight (E)

Vacuum Breaker

Less (XYV)

Special Features

Whitworth Thread (WWT)

Compliances & Certifications

BAA Compliant

BABAA Compliant

UPC Certified

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard NAVAL 152 shown

DESCRIPTION

Naval Concealed Manual Water Closet Flushometer

FEATURES

- Non-hold-open oscillating handle, Bak-Chek™ control stop and self-cleaning Xpelor Metering By-Pass ensure reliable operation and accurate flush delivery
- Available with adjustable or ground joint supply stop (ground joint recommended for salt water applications)
- Factory set flush volume of either 1.6 gpf/6.0 Lpf or 3.5 gpf/13.2 Lpf with adjustment range of 1.5 gpf/5.7 Lpf to 7.0 gpf/26.5 Lpf
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Naval Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Concealed Flushometers Repair and Maintenance Guide](#)
- [Naval Repair and Maintenance Guide](#)
- [Additional Downloads](#)