

OPTIONS**Flush Volume**

0.125 gpf (0.5 Lpf) (0.125)

0.5 gpf (1.9 Lpf) (0.5)

1.0 gpf (3.8 Lpf) (1.0)

Water Efficiency

High Efficiency

Low Consumption

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard REGAL 186 XL CV shown

DESCRIPTION

Regal® Exposed Manual Urinal Flushometer

FEATURES

- Flush volumes start as low as 0.125 gpf/0.5 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents urinal from exceeding intended flush volume
- Low Consumption flush accuracy controlled by Para-Flo™ technology
- Integrity of the product is maintained with control stop plug
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [B-73-A CV Flushometer Handle](#)
- [Regal XL Exposed Installation Instructions](#)
- [Regal Flushometers Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com