

OPTIONS

Flush Volume

- 1.1 gpf (4.2 Lpf) (1.1)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)

Finish

- Brushed Stainless (SF)
- Polished Chrome (CP)

Power Type

- Battery
- Battery with Hardwired Option

Activation

- Sensor

Valve

- Piston

Water Efficiency

- High Efficiency
- Low Consumption

Bypass

- Filtered

Fixture Type

- Water Closet

Fixture Connection

- Rear Spud

Installation

- Concealed

Override

- Electrical

Control Stop

- Integrated

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BREEAM Water Credit
- EPD
- Green Globes Water Credit
- HPD
- LEED Materials & Resources EPD Credit
- LEED Materials & Resources HPD Credit
- UPC Certified



Image for a standard TRF 8156 shown

DESCRIPTION

TruFlush Concealed Sensor Water Closet Flushometer

FEATURES

- True flushometer provides accurate flush volume
- Heavy-duty rough brass valve body
- Battery powered infrared sensor provides hands free activation
- Vandal-resistant wall plate with electronic override button
- Replaceable piston assembly accessible through front wall plate
- Concealed shut off sleeve adjusts flow rate
- **Not available in USA or Canada**
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass

DOWNLOADS

- [TruFlush Sensor Installation Instructions](#)
- [TruFlush Sensor Installation Instructions \(Spanish\)](#)
- [TruFlush Sensor Repair and Maintenance Guide](#)
- [Additional Downloads](#)

VIDEOS

-  TruFlush
-  TruFlush Installation
-  TruFlush Maintenance
-  TruFlush Flush Line

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

WaterSense Listed

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.