



DropSpot™ Bottle Filler

DRS100-UNFIL-REF-SS

Product description

Unfiltered, Refrigerated, 304 Stainless Steel,
DropSpot™ On-wall Bottle Filler.

Compliances & Certifications



(ASME A112.18.1 Compliant, IAPMO listed ASME, IGC 115, IGC 226, Meets Canada OBC and QBC, NSF-61/CAN-61, NSF-372 Lead Free, Proposition 65, Level 1.0 - NSF 61, TAS, UL 399/CSA C22.2 No.120)

Code 33820001

Finish



304 Stainless Steel (SS)

Downloads

- [↗ DRS100-REF Stand Alone Refrigerated Bottle Filler Installation Instructions.pdf](#)
- [↗ DRS100-UNREF Stand Alone Unrefrigerated Bottle Filler Installation Instructions.pdf](#)
- [↗ FA3000-DRS100 Filter Assembly Installation Instructions.pdf](#)
- [↗ RC8000 Remote Chiller for DRS-100 Bottle Filler Installation Instructions.pdf](#)
- [↗ FC3000 Replacement Water Filter Cartridge Installation Instructions.pdf](#)
- [↗ Additional Downloads](#)

Videos

- [▶ Sloan DropSpot™ Bottle Fillers and Water Coolers](#)
- [▶ Sloan DropSpot™ Bottle Fillers and Water Coolers Now at Wrigley Field](#)

Details

- Mounting: On-wall
- Configuration: Bottle Filler
- Filter Option: Unfiltered (REF)
- Refrigeration Option: Refrigerated (UNFIL)
- Finish: 304 Stainless Steel (SS)
- Chilling Capacity: 8.0 gph (30.3 lph)
- Full Load Amps: 5.3
- Length: 7.9 (201mm)
- Width: 19 (483mm)
- Height: 51.4 (1306mm)
- Weight: 106lbs (48kg)
- Installation Location: Indoor
- Bottle Filler Water Flow Rate: Up to 1.2 gpm (4.5 Lpm)

Features

- Touch-free sensor operated bottle filler with 20 second max run time
- ADA compliant when installed properly
- Up to 1.2 gpm fill rate for quick fill
- Swing-open cabinet provides easy access to filter
- Laminar flow water supply
- Soft ambient white light to indicate filter status
- Backlit LED light that illuminates bottle filling area when sensor is activated
- Bottle Counter Display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking
- Rough-in matches other manufacturers' recommended rough-in locations for easy replacement
- Prop 65 compliant
- OPTIONAL: A water filter upgrade can be added to this unit (part number 33830001). Sold separately
- Chilling capacity of 8.0 gph of 50F drinking water, based on 80F inlet water and 90F ambient
- Refrigerant R-134A

Recommended specifications

Sloan's DropSpot™ On-wall Bottle Filler Unfiltered Refrigerated Stainless. Chilling capacity of 8.0 gph of 50F drinking water, based on 80F inlet water and 90F ambient. Bottle filler shall include sensor operated activation with a 20 second maximum run time. Bottle counter display indicates the number of 16 oz plastic bottles saved as well as the ounces of water dispensed for water consumption tracking. White light indicates the water filter status. Unit shall include LED lights that illuminate the bottle filling area. Bottle filler housing construction shall be stainless steel with a satin finish. Bottle filler shall provide up to 1.2 gpm flow rate with a laminar flow. Cabinet door shall have swing-open mechanism, providing easy access for filter replacement.

Power

- (Standard) 115VAC
- 60Hz
- 5.3A
- Provide Duplex Receptacle on GFCI Protected Circuit

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

