



Variation Not Shown: Less Ground Joint

## G2 Sensor Flushometer

G2 8121-1.6-CP

### Product description

1.6 gpf, Polished Chrome Finish, Fixture Connection Rear Spud, Single Flush, Battery, G2 Exposed Sensor Water Closet Flushometer.

### Compliances & Certifications



(ADA Compliant\*, BAA Compliant, IAPMO, cUPC Certified)

### Code 3250440

#### Finish

 Polished Chrome (CP)

#### Downloads

-  [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions duplicate.pdf](#)
-  [G2 Repair and Maintenance Guide.pdf](#)
-  [Control Stop Repair and Maintenance Guide.pdf](#)
-  [Additional Downloads](#)

#### Videos

-  [Sloan - Company Overview](#)

Details

- Flush Volume: 1.6 gpf (6.0 lpf)
- Finish: Polished Chrome (CP)
- Power Type: Battery
- Valve: Diaphragm
- Valve Body Material: Semi-red Brass
- Fixture Type: Water Closet
- Fixture Connection: Rear Spud

Features

- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Recommended specifications

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

Valve Operating Pressure (Flowing)

15-80 psi (103 - 552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

Battery Specifications

| Usage     | 4-AA Battery Service Life† |        |         |       |
|-----------|----------------------------|--------|---------|-------|
|           | 14.5 yrs                   | 12 yrs | 7.2 yrs | 6 yrs |
| per month | 500                        | 1,000  | 3,000   | 4,000 |
| per day   | 25                         | 50     | 150     | 200   |

† Service life varies according to actual usage and restroom conditions  
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

\*Compliant with ADA accessibility requirements when installed according to ADA standards.

Looking for other variations of the G2 8121 product? [View the general spec sheet with all options.](#)  
[Find a compatible urinal](#) for this flushometer.  
[Find a compatible water closet](#) for this flushometer.

