

OPTIONS**Flush Volume**

3.5 gpf (13.2 Lpf) (3.5)

1.6 gpf (6.0 Lpf) (1.6)

Finish

Polished Chrome (CP)

Rough Brass

Water Efficiency

Water Saver

Low Consumption

L Dimension

10 ¾" (273mm) (10-3/4-LDIM)

11 ¾" (298mm) (11-3/4-LDIM)

7 ¾" (197mm) (7-3/4-LDIM)

Compliances & Certifications

BAA Compliant

BABAA Compliant

UPC Certified

cUPC Certified

NOTESFor product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ROYAL 151 shown

DESCRIPTION

Royal® Concealed Manual Water Closet Flushometer

FEATURES

- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan Concealed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Additional Downloads](#)