



Sloan XLERATOR® Hand Dryer

EHD-501-ECO-CN

Product description

EHD-501-ECO, 110/120V, Carbon Neutral, Sloan XLERATOR® Sensor-Operated Wall-Mounted Hand Dryer.

Compliances & Certifications



(BAA Compliant, Carbon Neutral^)

Code 3366074T

Finish

 Matte White (MW)

Downloads

-  Sloan XLERATOR and Sloan XLERATOR Eco Hand Dryer Instructions .pdf
-  Sloan Hand Dryers Brochure.pdf
-  Additional Downloads

Videos

-  Sloan – Company Overview

Details

- Finish: Matte White (MW)
- Voltage: 110/120V
- Wattage: 530 Watts
- Amperage: 4.3A-4.5A
- Mounting: Wall-Mounted
- Power Type: Hardwired
- Depth: 12.688" (170mm)
- Height: 12.688" (322mm)
- Width: 11.75" (298mm)

Features

- 35-second lockout feature if hands are not removed, 10 second dry time
- 95% cost savings vs. paper towels, Adjustable speed and sound (High-Low)
- Electric Specifications: 110-120V – 4.3-4.5 Amps, 460-530 Watts, 50/60 Hz, Can install multiple units on one circuit
- Externally visible Red LED light that flashes error codes to assist in troubleshooting and identify if filter has been clogged
- Hygienic hand drying solution, No Heat option
- Quantity Recommendations: 1 dryer for every 2 sink stations is sufficient for most applications. For high traffic applications we suggest 1 dryer per sink station.
- Suggested Mounting Heights for Ideal Performance (from floor to bottom of dryer): Men: 45" (114 cm), Women: 43" (109 cm), Teenagers: 41" (104 cm), Children: 35" (89 cm), ADA: 37" (94 cm).
Note: When mounting for any user ensure that it is mounted below the 48" ADA Maximum
- Vandal resistant cover design, Virtually maintenance free
- Weight: 15-17 lbs.

Recommended specifications

Sloan Xlerator Eco Sensor Operated Hand Dryer. 120V/110V Matte White Finish.

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

^To obtain the certificate for your carbon-neutral products, please reach out to Sloan's customer support:customer.service@sloan.com.

