



## G2 Sensor Flushometer

### G2 8111 BT

#### Product description

G2 Exposed Sensor Water Closet Flushometer.

#### Compliances & Certifications



(ADA Compliant, BAA Compliant, BABAA Compliant, cUPC Certified, IAPMO, LEED Water, Satisfies LEED Credits)

Listed compliances and certifications may vary based on product variation.

#### Finish







Available in Polished Chrome (CP), Graphite (GR), Brushed Stainless (SF), Brushed Nickel (BN), Polished Brass (PB).

#### Connectivity

 Bluetooth with Sloan Connect App

#### Downloads

-  G2 and ECOS Single Flush Optima Plus Valve Installation Instructions duplicate
-  G2 Repair and Maintenance Guide
-  Special Finishes Brochure
-  Additional Downloads

#### Videos

-  Sloan – Company Overview

Features

- Wireless connected device for real time diagnostic and adjustable product settings
- Sloan Connect App® readily available for smart phone and tablet devices
- User friendly three (3) second Flush Delay
- “Low Battery” Flashing LED
- Sweat solder adapter with cover tube and cast wall flange with set screw
- Four (4) Size AA Battery Power Source
- Operates by means of an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Engineered Metal Cover with replaceable Lens Window
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Courtesy Flush® Override Button
- High copper, low zinc brass castings for dezincification resistance
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037

Battery Specifications

| Usage     | 4- AA Battery Service* Life |        |         |       |
|-----------|-----------------------------|--------|---------|-------|
|           | 15.2 yrs                    | 13 yrs | 8.3 yrs | 7 yrs |
| per month | 500                         | 1,000  | 3,000   | 4,000 |
| per day   | 25                          | 50     | 150     | 200   |

\* Service life varies according to actual usage & restroom conditions  
Battery shelf life: Alkaline= ~10 years - Lithium= ~25 years

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

Compatible products



**ST-2009**  
Vitreous China Wall-Mounted Water Closet

[View product >](#)



**ST-2459**  
Vitreous China Wall-Mounted Water Closet

[View product >](#)

Featured projects



**Climate Pledge Arena**  
Seattle, WA

[View project >](#)



**Inova Fairfax Hospital**  
Falls Church, VA

[View project >](#)


Featured collections



**Halsted Street®**  
Classic materials and hands-free convenience

[View collection >](#)


Featured room ideas



**Coworking Space**  
Form and function take center stage with this room idea for coworking spaces.


[View room idea >](#)

Featured markets



**Education**  
Campus-wide hygiene and hydration that's easy to maintain and built to last.

[View featured market >](#)



**Hospitality**  
Reliable performance and elevated aesthetics provide guests a stellar experience.

[View featured market >](#)

