

OPTIONS**Flush Volume**

- 1.6/3.5 gpf (6.0/13.2 Lpf) (1.6/3.5)
- 2.4 gpf (9.1 Lpf) (2.4)
- 1.28 gpf (4.8 Lpf) (1.28)
- 1.6 gpf (6.0 Lpf) (1.6)
- 4.5 gpf (17 Lpf) (4.5)

Finish

- Polished Chrome (CP)

Power Type

- Battery
- Hardwired (HW)

Activation

- Sensor

Valve

- Diaphragm

Water Efficiency

- Water Saver
- High Efficiency

Fixture Type

- Water Closet

Fixture Connection

- Top Spud

Installation

- Exposed

Override

- Electrical

Handle

- Less Handle Body (LH)

Control Stop

- Adjustable Ground Joint for Tek (XDT)

Special Features

- Fits †Zurn® valve bodies (Z)

Specialty

- Retrofit

Compliances & Certifications

- ADA Compliant
- BAA Compliant
- BABAA Compliant



Image for a standard G2 RESS-C shown

DESCRIPTION

G2 Exposed Sensor Water Closet Retrofit Flushometer

FEATURES

- Valve shall be in compliance to the applicable sections of ASSE 1037

DOWNLOADS

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Sloan Optima Plus Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

UPC Certified
cUPC Certified
BREEAM Water Credit
Green Globes Water Credit
Satisfies LEED Credits
cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.