



## Elongated Floor-Mounted Standard Water Closet

ST-2009-CN

### Product description

Carbon Offset, Vitreous China Floor-Mounted Standard Water Closet.

### Compliances & Certifications



(BREEAM Materials Credit, CalGreen Compliant, Carbon Neutral, Carbon Offset, CEC Compliant, cUPC Certified, EPD, Green Globes Credit, HPD, IAPMO, LEED Credit, LEED HPD, Satisfies LEED Credits, EPA WaterSense Listed, WELL Building Standard)

### Code 2102009T

#### Downloads

- [HET Top Spud Installation Instructions.pdf](#)
- [SS:ST:SU:WETS:WEUS Fixtures Repair and Maintenance Guide.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

#### Videos

- [Sloan - Company Overview](#)

---

## Details

- Flush Volume: 1.1-1.6 gpf (4.2-6 lpf)
- RIM Height: 15.00" (15.00 mm)
- Nominal Dimensions: 26.75" x 14" x 15" (679 x 356 x 381mm)

---

## Features

- Designed to maximize and complement Sloan flushometers
- Universal model works with Sloan flushometers from 1.1 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Syphonjet flushing achieves 1000g Map Scores when used with Sloan flushometers
- IAPMO certified to meet or exceed ASME A112.19.2 standards
- WaterSense compliant when used with a WaterSense compliant flushometer

---

## Recommended Seats

- Bemis - 1955CT/1955SSCT & 2155CT/2155SSCT
- Church - 295CT/295SSCT & 2155CT/2155SSCT

---

## Plumbing System Requirements

- Minimum Flowing Pressure: 25 PSI (172 kPa)
- Maximum Static Pressure: 80 PSI (552 kPa)

---

## Warranty

[View Warranty Information](#)

---

## Notes

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

[Find a compatible flushometer](#) for this water closet

WaterSense compliant when used with a WaterSense compliant flushometer.

