

OPTIONS

Flush Volume

1.28/1.1 gpf (4.8/4.2 Lpf) (1.28/1.1) 1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)

Finish

Brushed Nickel (BN)
Brushed Stainless (SF)

Graphite (GR)

Polished Brass (PB)

Polished Chrome (CP)

Water Efficiency

High Efficiency Low Consumption

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

UPC Certified

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed


cUPC Certified

cUPC Green Certified

NOTES

For product line drawings, view model-specific spec sheets.

All information contained within this document subject to change without notice.



DESCRIPTION

ECOS® Exposed Sensor Water Closet Flushometer

FEATURES

- Wireless connected device for real time diagnostic and adjustable product settings
- Sloan Connect App® readily available for smart phone and tablet devices
- User friendly three (3) second Flush Delay
- "Low Battery" Flashing LED
- Sweat solder adapter with cover tube and cast wall flange with set screw
- Four (4) Size AA Battery Power Source
- Operates by means of an infrared sensor with multiplefocused, lobular sensing fields for high and low target detection
- Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flex Tube Diaphragm designed for improved life and reduced maintenance
- Engineered Metal Cover with replaceable Lens Window
- PERMEX® Synthetic Rubber Diaphragm with Dual-Filtered Fixed Bypass
- Courtesy Flush® Override Button
- High copper, low zinc brass castings for dezincification resistance
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSF 1037



DOWNLOADS

- Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Additional Downloads

VIDEOS

- Sloan Connect App®
- PVD Special Finishes