



Elongated Floor-Mounted Rear Outlet Water Closet

ST-2539-LR

Product description

Standard, Vitreous China Floor-Mounted Rear Outlet Water Closet.

Compliances & Certifications



(ADA Compliant*, cUPC Green Certified, IAPMO, EPA WaterSense Listed)

Code 2112539

Downloads

- [ST-2539 Installation Instructions.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Details

- Flush Volume: 1.28-1.6 gpf (4.8-6 lpf)
- RIM Height: 16.50" (419 mm)
- Nominal Dimensions: 29.625" x 15" x 16.5" (752 x 381 x 419mm)

Features

- Designed to maximize and complement Sloan flushometers
- Universal model works with Sloan flushometers from 1.28 to 1.6 gpf
- Durable, hygienic vitreous china construction with elongated rim
- Designed for prisons and mental healthcare facilities
- IAPMO certified to meet or exceed ASME A112.19.2 standards

Plumbing System Requirements

- Minimum Flowing Pressure: 25 PSI (172 kPa)
- Maximum Static Pressure: 80 PSI (552 kPa)

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

*Compliant with ADA accessibility requirements when installed according to ADA standards.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

AttributePlainHyperlinks:Find a compatible flushometer for this water closet

WaterSense compliant when used with a WaterSense compliant flushometer.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

