



Royal® Sensor Flushometer

ROYAL 110 SFSM

Product description

Royal® Exposed Sensor Water Closet Flushometer.

Compliances & Certifications



(ADA Compliant, BAA Compliant)

Listed compliances and certifications may vary based on product variation.

Finish



Available in Polished Chrome (CP).

Downloads

- [Royal Exposed Installation Instructions](#)
- [Royal Exposed Spanish Installation Instructions](#)
- [EBV-500_550-A Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- <https://cdn.pimber.ly/public/asset/>
- [Additional Downloads](#)

Videos

- [Sloan – Company Overview](#)

Features

- True Mechanical Override Flush Button
- Four (4) size C batteries included
- “Low Battery” Flashing LED “User in View” Flashing LED
- 72-Hour Sentinel Flush
- Sweat solder adapter with cover tube and cast wall flange with set screw
- No External Volume Adjustment to Ensure Water Conservation
- Infrared Sensor with Multiple-focused, Lobular Sensing Fields for high and low target detection
- 1” I.P.S. Screwdriver Bak-Chek® Angle Stop with Free Spinning Vandal Resistant Stop Cap
- Diaphragm, Stop Seat and Vacuum Breaker to be molded from PERMEX® rubber compound for Chloramine resistance

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.