

OPTIONS

Flush Volume

1.6/1.1 gpf (6.0/4.2 Lpf) (1.6/1.1)

Finish

Polished Chrome (CP)

Power Type

Battery

Activation

Sensor

Valve

Diaphragm

Water Efficiency

High Efficiency

Fixture Type

Water Closet

Fixture Connection

Top Spud

Installation

Exposed

Override

Electrical

Control Stop

1"

Inlet

1"

Compliances & Certifications

ADA Compliant
BAA Compliant
BABAA Compliant
BREEAM Water Credit
Green Globes Water Credit
cUPC Certified
cUPC Green Certified

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard ECOS 8113 shown

DESCRIPTION

ECOS® Exposed Sensor Water Closet Flushometer

FEATURES

- Automatically initiates a 1.1 gpf or 1.6 gpf flush based on how long user remains in sensor range, Buttons on top of the flush valve enable manual flushing with a standard or reduced flush at restroom visitor's discretion
- Deploys an infrared sensor with multiple-focused, lobular sensing fields for high and low target detection
- User-friendly, three-second flush delay
- High copper, low zinc brass castings for dezincification resistance
- Fixed metering bypass and no external volume adjustment to ensure water conservation
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan ECOS Single/Dual-Flush Flushometer & Retrofit Valve Installation Instructions](#)
- [Sloan Ecos Valve \(Spanish\) Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [ECOS Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com