

**OPTIONS****Flush Volume**

- 0.5 gpf (1.9 Lpf) (0.5)
- 1.0/1.5 gpf (3.8/5.7 Lpf) (1.0/1.5)
- 0.25 gpf (0.9 Lpf) (0.25)
- 1.0 gpf (3.8 Lpf) (1.0)
- 3.5 gpf (13.2 Lpf) (3.5)

**Finish**

- Polished Chrome (CP)

**Power Type**

- Battery
- Hardwired (HW)

**Activation**

- Sensor

**Valve**

- Diaphragm

**Water Efficiency**

- High Efficiency

**Fixture Type**

- Urinal

**Fixture Connection**

- Top Spud

**Installation**

- Exposed

**Override**

- Electrical
- Less (L/OR)

**Control Stop**

- Adjustable Ground Joint for Tek (XDT)
- No (XD)

**Special Features**

- Fits †Zurn® valve bodies (Z)
- Less Logo (LL)

**Specialty**

- Retrofit

**Compliances & Certifications**

- ADA Compliant
- BAA Compliant
- Satisfies LEED Credits
- cUPC Certified



Image for a standard G2 RESS-U shown

**DESCRIPTION**

G2 Exposed Sensor Urinal Retrofit Flushometer

**FEATURES**

- Valve shall be in compliance to the applicable sections of ASSE 1037

**DOWNLOADS**

- [G2 and ECOS Single Flush Optima Plus Valve Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Sloan Optima Plus Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

BABAA Compliant  
BREEAM Water Credit  
Green Globes Water Credit  
cUPC Green Certified

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.

† The brands and/or products names referenced herein may be subject to trademark rights of their respective owners. Use of the brands and names is for identification purposes only and does not imply affiliation with or endorsement by Sloan.