

OPTIONS

Flush Volume

1.28 gpf (4.8 Lpf) (1.28)

1.6 gpf (6.0 Lpf) (1.6)

Water Efficiency

High Efficiency

Low Consumption

Bypass

Dual-Filtered Fixed Bypass Diaphragm

Override

Electrical

True Mechanical (TMO)

Wall Box

Small (SWB)

With (W/BOX)

Compliances & Certifications

ADA Compliant

BAA Compliant

BABAA Compliant

UL Certified

UPC Certified

cUPC Certified

BREEAM Water Credit

CalGreen Compliant

Green Globes Water Credit

LEED V4 Water Efficiency Credit

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.



Image for a standard SLOAN 140 ESS shown

DESCRIPTION

Sloan® Concealed Sensor Hardwired Water Closet Flushometer

FEATURES

- Sensor-activated, hardwired closet flushometer
- High Chloramine Resistant PERMEX® Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- High chloramine resistant PERMEX synthetic rubber diaphragm with Linear Filtered Bypass and Vortex Cleansing Action
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [Sloan/Regal Concealed and Exposed Sensor Installation Instructions](#)
- [Optima ESS Repair and Maintenance Guide](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Optima ESS TMO SWB Concealed Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

VIDEOS



ESS Flushometer