Accessory

VBF-72-A1 TRAP PRIMER 1.6 GPF 116/116

Product description

VBF-72-A Vacuum Breaker Trap Primer.

Compliances & Certifications

(IAPMO, UPC Certified)

Code 3396078

Downloads

- Trap Primer Installation Instructions.pdf
- Vacuum Breaker Trap Primer Repair and Maintenance Guide.pdf
- Additional Downloads

Videos

- Sloan – Company Overview

WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Sloan 10500 Seymour Ave, Franklin Park 800.982.5839 sloan.com

Features

- Vacuum Breaker Trap Primer 1.6 gpf 116/116

Warranty

View Warranty Information

Notes

All information contained within this document subject to change without notice.

Model Number	Flush Connection Length "L"	Centerline of Supply to Top of Bowl "A"	Centerline of Supply to Trap Primer Outlet "B"	Critical Line to Trap Primer Outlet "C"
110/111 †	8½" (216 mm)	11½" (292 mm)	7" (178 mm)	2¼" (57 mm)
113	13" (330 mm)	16" (406 mm)	11" (280 mm)	6¼" (159 mm)
115	21" (533 mm)	24" (610 mm)	11" (280 mm)	6¼" (159 mm)
116	24 (610 mm)	27" (696 mm)	11" (280 mm)	6¼" (159 mm)

† Check with local codes for approval to use VBF-72-A1 Trap Primer with Model

When ordering a Sloan Flushometer with a Trap Primer, please specify the "TP" Variation; e.g., Model Number 110 TP.